



Technical
Info


Whiteboard Painting Instructions for tabrasa™



1. Clean surface thoroughly with soap and water
Use acetone or other solvent if needed



2. For tabrasa™ prime surface with Kilz Premium Water Based Primer



3. Sand smooth primed surface with medium to fine grit (120-150) sandpaper
Clean off all dust using a clean dry cloth



4. Apply tabrasa™ according to the installation instructions

Instructions:

1. Clean surface thoroughly with soap and water
Use Acetone or other solvent to remove tape, ink, or other surface materials
2. Prime surface with Kilz Premium Water Based Primer
3. Sand smooth primed surface with medium to fine grit (120-150) sandpaper
Clean off all dust using a clean dry cloth
4. Apply tabrasa™ according to the installation instructions

Whiteboard Painting Instructions for tabrasa™



Technical
Info

Chalkboard Painting Instructions for tabrasa™




1. Clean surface thoroughly with soap and water

Use acetone or other solvent if needed



2. For tabrasa™ prime surface with Kilz Premium Water Based Primer or Sherwin-Williams Multi-Purpose Latex Primer



3. Sand smooth primed surface with medium to fine grit (120-150) sandpaper

Clean off all dust using a clean dry cloth



4. Apply tabrasa™ according to the installation instructions

Instructions:


1. Clean surface thoroughly with soap and water
Use Acetone or other solvent to remove tape, ink, or other surface materials
2. Prime surface with Kilz Premium Water Based Primer or Sherwin-Williams Multi-Purpose Latex Primer
3. Sand smooth primed surface with medium to fine grit (120-150) sandpaper
Clean off all dust using a clean dry cloth
4. Apply tabrasa™ according to the installation instructions

Chalkboard Painting Instructions for tabrasa™



Technical
Info


Painting Instructions for Over Existing IdeaPaint/tabrasa™



1. Scuff Surface with Medium Grit Sandpaper (80-120 grit)



2. Prime Surface with Kilz Premium Water Based Primer



3. Sand Smooth Primed Surface with Medium to Fine Grit (120-150) Sandpaper
Clean Off All Dust using a clean Dry Cloth



4. Apply tabrasa™ According to the Installation Instructions

Instructions:

1. Scuff surface with medium grit sandpaper (80-120 grit)
2. Prime surface with Kilz Premium Water Based Primer
3. Sand smooth primed surface with medium to fine grit (120-150) sandpaper
Clean off all dust using a clean dry cloth
4. Apply tabrasa™ according to the installation instructions

Painting Instructions for Over Existing IdeaPaint/tabrasa™




Technical
Info

Galvanized & Ungalvanized Steel Painting Instructions for tabrasa™




1. Clean surface
thoroughly with
soap and water

Use acetone or
other solvent if
needed



2. For tabrasa™
Prime surface
with
Sherwin-Williams
Surface
Enamel (solvent
based)



3. Sand smooth
primed surface
with medium to
fine grit (120-150)
sandpaper

Clean off all dust
using a clean dry
cloth



4. Apply tabrasa™
according to
the installation
instructions

Instructions:





1. Clean surface thoroughly with soap and water
Use acetone or other solvent to remove tape, ink, or other surface materials
2. Prime surface with Sherwin-Williams Surface Enamel (solvent based)
3. Sand smooth primed surface with medium to fine grit (120-150) sandpaper
Clean off all dust using a clean dry cloth
4. Apply tabrasa™ according to the installation instructions

Galvanized & Ungalvanized Steel Painting Instructions for tabrasa™



Technical
Info

Glass Surface Painting Instructions for tabrasa™

 <p>1. Clean Surface with Acid / Acetone Wipes</p>	 <p>2. For tabrasa™ Prime with Kilz Premium Water Based Primer</p>	 <p>3. Sand Smooth Primed Surface with Medium to Fine Grit (120-150) Sandpaper Clean Off All Dust using a clean Dry Cloth</p>	 <p>4. Apply tabrasa™ According to the Installation Instructions</p>
---	---	--	---

Instructions:

1. Clean surface with acid/acetone wipes
2. Prime surface for tabrasa™ with Kilz Premium Water Based Primer
3. Sand smooth primed surface with medium to fine grit (120-150) sandpaper
Clean off all dust using a clean dry cloth
4. Apply tabrasa™ according to the installation instructions

Glass Surface Painting Instructions for tabrasa™